

When traversing dictionaries, the corresponding key and value can be retrieved at the same time using the `items()` method. This method transforms the dictionary to `dict_items` (don't confuse `dict_items` with lists).

```
print(dictionar_capitale.items()) # dict_items([('Bucharest', 'RO'), ('Budapest', 'Hungary'), ('Chisinau', 'Moldova')])
```

To get the list of all keys, use the `keys()` method. For values, use the `values()` method:

```
print(dictionar_capitale.keys()) # dict_keys(['Bucharest', 'Budapest', 'Chisinau'])
print(dictionar_capitale.values()) # dict_values(['RO', 'Hungary', 'Moldova'])
```

Traversing dictionaries using the `reduce()` function:

```
student_grade = { 'Alex': 10, 'Mihai': 9, 'Ioana': 10}

print(student_grade.items()) # dict_items([('Alex', 10), ('Mihai', 9), ('Ioana', 10)])

def function_sum(sum, student):
    name, grade = student # we unpack each tuple received as a
                          # parameter (example: ('Alex', 10))
    return sum + grade

import functools
def student_average(dictionary):
    sum_notes = functools.reduce(function_sum,
                                 dictionary.items(), 0)
    return sum_notes / len(dictionary) # the length of a
    # dictionary (the number of elements) is obtained
    # with the help of the len function

print(student_average(student_grade))
```

Traversing dictionaries recursively

For traversing dictionaries recursively, we convert the dictionary received as a parameter into `'dict_items'`, then we convert `'dict_items'` into a list that we will traverse recursively.

```

def recursive_sum(dict_list):
    if len(dict_list) > 0:
        name, note = dict_list[0]
        return note + recursive_sum(dict_list[1:])
    else:
        return 0

def medie_elevi_recursiva(dictionary):
    suma_notes = suma_recursiva(list(dictionary.items())) # the
dictionary received as a parameter is converted to dict_items,
then to list
    return suma_notes/len(dictionary)

print(recursive_student_average(student_grade))

```

Solved exercises with dictionaries

Write a function that takes a list of tuples (string, integer) and creates a dictionary where each string is associated with the sum of all the values it is associated with in the list.

Example:

Input: [("Ana",7), ("Alin",3), ("Ana",9)]

Output: {'Ana': 16, 'Alin': 3}

```

def transform(list, dictionary = {}):
    if (list == []):
        return dictionary
    if(list[0][0] in dictionary):
        dictionary[list[0][0]] = list[0][1] +
dictionary[list[0][0]]
    else:
        dictionary[list[0][0]] = list[0][1]
    return transform(list[1:],dictionary)

lst = [("Ana",7), ("Alin",3), ("Ana",9)]
print(transform(lst))

```