

Computer Programming

## Input/output functions

Marius Minea

marius@cs.upt.ro

7 November 2016

# All inputs must be checked!

A program will not always receive the data it asks for

User may make *mistakes*, or may be **evil**

⇒ program *must check* that data was read correctly

**MUST check** *return code* of input function (NOT just value read)

Avoid **overflow** when reading *strings* and arrays

*stop* reading when array limit is reached

Buffer overflows *corrupt memory* (program data)

⇒ system is *vulnerable* to **intruder attacks**

Unvalidated input may cause *code injection* (attacker runs code)

⇒ some of the most **dangerous and costly** errors

A badly written program  
An ignorant programmer are *worse* than no program(mer) at all!

## Always check input was successful (and correct)!

You can only *ask* to read data, the call may not succeed:  
system: no more data (end-of-file), read error, etc.  
user: data not in needed format (illegal char, not number, etc.)

I/O functions report both a *result* and an *error code*:

1. *expand result datatype* to include error code  
getchar() : unsigned char converted to int,  
or EOF (-1) which is different from any unsigned char
2. return type may have a special *invalid/error value*  
fgets returns address where the line was read (first argument)  
or NULL (invalid pointer value) when nothing read
3. return *error code* and *store result* at given pointer  
scanf *returns no. of items read* (can be 0, or EOF at end-of-input)  
takes as arguments *addresses* where it should place read data

## Review: I/O for one char

*Read:* `int getchar(void);`

*Call (use):* `getchar()` no parameters

Returns an **unsigned char** converted to **int**,  
or EOF (negative, usually -1) if no char could be read

*Un-read:* `int ungetc(int c, FILE *stream);`

puts a character `c` back into a given input stream (file).

for standard input: `ungetc(c, stdin);`

DON'T *ungetc* more chars at once (effect not guaranteed);

must read between successive calls to `ungetc`

*Print a char:* `int putchar(int c);`

writes an **int**, converted to **unsigned char** to `stdout`;

returns its value, or **EOF** (constant -1) on error

DON'T `putchar(-1)` : -1 is converted to 255 (an actual char)

All input/output functions: in `stdio.h` (unless noted)

## Read a text line: fgets

*Declaration:* `char *fgets(char *s, int size, FILE *stream);`

Reads up to and including newline `\n`, max. `size-1` characters, stores line in array `s`, adds `'\0'` at the end.

```
char tab[80];
if (fgets(tab, 80, stdin)) { /* line has been read */ }
else { /* nothing read, likely EOF */ }
```

Third parameter to `fgets` indicates the *file* from which to read: `stdin` (`stdio.h`) is *standard input* (keyboard unless redirected)

**WARNING!** NO reading without checking!

Check successful return code, anything else is too late!

`fgets` returns `NULL` if nothing read (end-of-file).

if successful returns address passed as argument (thus non-null)

⇒ Test *non-null* result to find out if read successful

## Read line by line until end of input

```
char s[81];  
while (fgets(s, 81, stdin)) printf("%s", s);
```

A line with > 80 chars will be read and printed piecewise (OK!)

More complex: can test if read line was truncated:

```
int c; char s[81];  
if (fgets(s, 81, stdin)) // line was read  
    if (strlen(s) == 80 && s[79] != '\n' // unfinished  
        && ((c = getchar()) != EOF) { // EOF not reached  
        printf("incomplete line: %s\n", s);  
        ungetc(c, stdin); // put char c back  
    } else printf("complete line: %s\n", s);
```

C11 standard **removed** function ~~gets~~: did not limit size read

⇒ it is **impossible** to use ~~gets~~ safely

⇒ **buffer overflow, memory corruption, security vulnerabilities**

## Print a string

*Declaration:* `int puts(const char *s);`

prints string `s` followed by newline `\n`

```
puts("text; newline will be added");
```

*Declaration:* `int fputs(const char *s, FILE *stream);`

prints string `s` to given output stream

```
fputs("text with no newline added", stdout);
```

```
fputs(s, stdout); is like printf("%s", s);
```

prints string `s` as is, without additional newline

`stdout` is *standard output* (screen unless redirected)

`puts` and `fputs` return EOF on error, nonnegative on success

## Review: printf (formatted output)

```
int printf(const char* format, ...);
```

functions with variable number of parameters: discussed later

First parameter: the *format string*; may contain:

usual characters (are printed)

*format specifiers*: % and a letter:

%c char, %d, %i decimal, %e, %f, %g real, %o octal, %p pointer,  
%s string, %u unsigned, %x heXadecimal

Remaining parameters: *expressions*, their *values* are printed

their number and type must correspond to format specifiers

Result: number of characters printed (usually not used/ignored)

Example:

```
printf("square root of %d is %fn", 3, sqrt(3));
```

## Formatted input: read numbers

```
int scanf(const char* format, ...);
```

First arg: *string*, with format specifiers (some [differences to printf!](#))

Remaining parameters: *addresses* where to store read values

Need *addresses*, NOT necessarily `&` (one way to get addresses)  
DON'T use `&` for strings: array name IS already its address

*Returns number* of objects read (assigned) (NOT their value!)  
or EOF when error/end-of-file reached *before* anything read

Read one integer:

```
int n;  
if (scanf("%d", &n) == 1) // one number read  
    printf("number read: %d\n", n);  
else puts("could not read number");
```

## More numbers with scanf

*Format specifiers*: like for printf

`%u` unsigned    `%o` octal    `%x` hexadecimal    `%i` any int format

**CAUTION!** `%f` float    `%lf` double    (same in printf)

Reading numbers *consumes and ignores* any initial *whitespace*

Like in printf, can combine arbitrary formats

**WARNING!** **MUST CHECK** scanf return value!

(number of objects read successfully)

```
double x; float y;    // CAUTION : %f float %lf double
if (scanf("%lf%f", &x, &y) != 2) { /* handle error */ }
else { /* can use x, y */ }
```

## Read a word with scanf

Format letter **s**: for reading a *word* (string WITHOUT whitespace)  
**WILL NOT** read a sentence "This is a test."  
to read a line, use fgets

Arrays are ALWAYS limited!

⇒ **MUST** give max. length (a constant) *between* % and s  
one less than array length, scanf will add \0

**NEVER** use ~~%s: scanf("%s", ...)~~. Leads to **buffer overflow**.

```
char word[33];  
if (scanf("%32s", word) == 1)  
    printf("Word read: %s\n", word);
```

scanf with s format *consumes and ignores* initial *whitespace*:  
\t \n \v \f \r and space, as checked by isspace()

**CAUTION!** Array names *are addresses*, DON'T use &

**CAUTION!** Format **s** reads a *word* (up to whitespace), *not a line!*

## Good practice: read and process while successful

For repeated processing (while input matches format), write:

```
while (read successful) process data
```

```
while (fgets(...)) { /*process line */
```

```
while ((c = getchar()) != EOF) { /*process c */
```

```
while (scanf(...) == how-many-to-read) { /*use them*/
```

On loop exit check: end-of-file? (nothing more), or (format) error.

```
int feof(FILE *stream);
```

returns nonzero if end-of-file reached for given stream

if feof(stdin) input is finished

else input does not match format  $\Rightarrow$  read next char(s) and report

*DON'T* use feof in read loop.

```
while (!feof(stdin))
```

```
scanf("%d", &n);
```

After last good read (number), end-of-input is not yet reached

unless nothing more (no whitespace, newline) after it

$\Rightarrow$  next read will not succeed, but is not checked

## Handling input errors

Simplest: *exit program*

primitive, but *incomparably better than continuing with errors*

`void exit(int status)` from `stdlib.h` ends program

Can write an error function that prints a message and calls `exit()`

```
#include <stdio.h>
#include <stdlib.h>
void fatal(char *msg)
{
    fputs(msg, stderr); // to screen unless redirected
    exit(EXIT_FAILURE); // or exit(1)
}
```

We can then use this function for *every* read:

```
if (scanf("%d", &n) != 1) fatal("error reading n\n");
// got here, use n
```

Good practice: Always print error messages to stderr

can separate errors from output (using redirection)

## Recovering from input errors

*CAUTION!* `scanf` *does not consume* non-matching input  
⇒ *must consume bad input* before trying again

```
int m, n;
printf("Input two numbers: ");
while (scanf("%d%d", &m, &n) != 2) { // while not OK
    for (int c; (c = getchar()) != '\n';) // skip to end of line
        if (c == EOF) exit(1);          // nothing more, done
    printf("try again: ");
}
// can use m and n now
```

## CAUTION: Check bounds when filling an array

Often, we have to fill an array up to some stopping condition:  
read from input upto a given character (period, \n, etc)  
copy from another string or array

Arrays must not be written beyond their length!

*Test array not full **before** filling element!*

```
for (int i = 0; i < len; ++i) { // limit to array size
    tab[i] = ...;           // assign with value if read successful
    if (some other stopping condition) break/return;
}
// here we can test if maximal length reached
// and report if needed
```

## scanf: matching ordinary chars in format

Besides format specifiers (%), format string may have *ordinary chars*

printf: printed as such

scanf: *must appear in input*

Example: reading calendar date in dd.mm.yyyy format

```
unsigned d, m, y;  
if (scanf("%u.%u.%u", &d, &m, &y) == 3)  
    printf("read 3 values: d=%u, m=%u, y=%u\n", d, m, y);  
else printf("error reading date\n");
```

input 5.11.2013 (with periods!)  $\Rightarrow$  d=5, m=11, y=2013

see later how to enforce *exactly* 2 or 4 digits

scanf reads until input *does not match* format

Non-matching chars are not read; those variables are not assigned

```
scanf("%d%d", &x, &y);  
input: 123A returns 1; x = 123, y: unchanged; input rest: A
```

```
scanf("%d%x", &x, &y);  
input: 123A returns 2; x = 123, y = 0xA (10)
```

## Reading strings with certain characters

*allowed characters*: between [ ] (ranges: with -)

Reading stops at first disallowed character

```
char a[33]; if (scanf("%32[A-Za-z_]", a) == 1) ...  
    max. 32 letters and _
```

```
char num[81]; if (scanf("%80[0-9]", num) == 1) ...  
    string of digits
```

**WARNING! MUST** give max. length between % and [ ]

Reading a string *except for disallowed (stopping) chars*:  
like above, but use ^ after [ to specify *disallowed* chars

```
char t[81]; if (scanf("%80[^\\n.]", t) == 1) ...  
    reads up to period or newline
```

**WARNING!** Format is [ ], NOT with s: %20[A-Z]s

## Reading a fixed number of chars

One character:

```
int c = getchar(); if (c != EOF) { /*read OK */}  
int c; if ((c = getchar()) != EOF) { /*read OK */}
```

With scanf (use char, not int; useful for arrays)

```
char c; if (scanf("%c", &c) == 1) { /* read OK */}
```

Reading a *fixed number of chars*:

```
char tab[80]; scanf("%80c", tab);  
reads EXACTLY 80 chars, anything (including whitespace)  
DOES NOT add '\0' at end ⇒ can't know if all read
```

Check how many read by initializing with zeroes and testing length:  
(or with %n format, see later)

```
char tab[81] = "";  
scanf("%80c", tab);  
int len = strlen(tab); // will be between 0 and 80
```

## Whitespace handling in scanf

*Numeric* formats and `s` consume and ignore initial whitespace

`"%d%d"` two ints separated and possibly preceded by whitespace

In formats `c` `[ ]` `[^ ]` whitespace are *normal chars* (not ignored)

A *white space* in the format consumes  $\geq 0$  whitespace in input  
`scanf(" ");` consumes whitespace until first non-space char

`"%c %c"` reads char, consumes  $\geq 0$  whitespace, reads other char

`"%d %f"` is like `"%d%f"` (whitespace allowed anyway)

**CAUTION!** `"%d "` : space after number consumes ALL whitespace  
(*including* newlines!)

Consume whitespace, but not newline `\n`:

`scanf("%*[\t\v\f\r ]");`

`*` modifier means consume and ignore (no address is given)

## Consume and ignore with scanf

To consume and ignore (skip) data with a given format:  
Use \* after %, without specifying address where to read  
⇒ scanf reads according to pattern, but does not store data  
and does not count in result (number of read objects)

Example: text with three grades and average, need just average:

```
int avg;  
if (scanf("%*d%*d%*d%d", &avg) == 1) { /* use */ }  
else { /* wrong format, handle error */ }
```

Example: consume rest of line

```
scanf("%*[^\\n]"); // consume up to \\n, without \\n  
if (getchar() == EOF) { /* end of input */ }  
// otherwise, getchar() has consumed \\n, continue
```

## Specifying limits in scanf

Number between % and format character limits count of chars read  
%4d int, at most 4 chars (initial spaces don't count, sign does!)

<code>scanf("%d%d", &amp;m, &amp;n);</code>	12 34	m=12 n=34
<code>scanf("%2d%2d", &amp;m, &amp;n);</code>	12345	m=12 n=34 rest: 5
<code>scanf("%d.%d", &amp;m, &amp;n);</code>	12.34	m=12 n=34
<code>scanf("%f", &amp;x);</code>	12.34	x=12.34
<code>scanf("%d%x", &amp;m, &amp;n);</code>	123a	m=123 n=0xA

## Format specifiers in scanf

`%d`: signed decimal int

`%i`: signed decimal, octal (0) or hexadecimal (0x, 0X) int

`%o`: octal (base 8) int, optionally preceded by 0

`%u`: unsigned decimal int (*warning*: accepts negative and converts)

`%x`, `%X`: hexadecimal int, optionally with 0x, 0X

`%c`: any char, including whitespace

`%MAXs`: string of chars, until first whitespace. '\0' is added

`%MAX[...]`: string of indicated allowed characters

`%MAX[^...]`: string except indicated disallowed chars

**MUST** have a *constant* **MAX** unless assignment suppressed with \*

`%a`, `%A`, `%e`, `%E`, `%f`, `%F`, `%g`, `%G`: real (possibly with exponent)

`%p`: pointer, as printed by printf

`%n`: writes into argument (int \*) count of chars read so far  
does not read; does not add to count of read objects (return value)

`%%`: percent character

## Format specifiers in printf

`%d`, `%i`: signed decimal int

`%o`: signed octal int, without initial 0

`%u`: unsigned decimal int

`%x`, `%X`: hexadecimal int, without 0x/0X; lower/upper case

`%c`: character

`%s`: string of characters, up to `'\0'` or indicated precision

`%f`, `%F`: real w/o exponent; 6 decimal digits; no dot if 0 precision

`%e`, `%E`: real with exponent; 6 decimal digits; no dot if 0 precision

`%g`, `%G`: real, like `%e`, `%E` if  $\text{exp.} < -4$  or  $\geq$  precision; else like `%f`.

Does not print zeroes or decimal point if useless

`%a`, `%A`: hexadecimal real with decimal 2's exponent `0xh.hhhhp±d`

`%p`: pointer, usually in hexadecimal

`%n`: writes into argument (`int *`) count of chars written so far

`%%`: percent character

## Formatting: modifiers

Format specifiers may have other *optional* elements:

*% flag size . precision modifier type*

<i>Flags:</i> *	field is read but not assigned (is ignored)	(scanf)
-	aligns value left for given size	(printf)
+	+ before positive number of signed type	(printf)
<i>space:</i>	space before positive number of signed type	(printf)
0	left-filled with 0 up to indicated size	(printf)

### *Modifiers:*

hh: argument is char (for `d i o u x X n` format) (1 byte)

`char c; scanf("%hhd", &c);`     in: 123 → c = 123 (1 byte)

h: argument is short (for `d i o u x X n` format), e.g. `%hd`

l: arg. long (format `d i o u x X n`) or double (fmt. `a A e E f F g G`)

`long n; scanf("%ld", &n); double x; scanf("%lf", &x);`

ll: argument is long long (for `d i o u x X n` format)

L: argument is long double (for `a A e E f F g G` format)

## Formatting: size and precision

*Size*: an integer

scanf: *maximal* character count read for this argument

printf: *minimal* character count for printing this argument

right aligned and filled with spaces, or according to modifiers

*Precision*: only in printf; dot . optionally followed by an integer  
(if only dot, precision is zero)

*minimal* number of digits for `diouxX` (filled with 0)

number of decimal digits (for `Eef`) / significant digits (for `Gg`)

printf("`|%7.2f|`", 15.234); | 15.23| 2 decimals, 7 total

*maximal* number of chars to print from a string (for `s`)

`char m[3]="Jan"; printf("%.3s", m);` (for string w/o `'\0'`)

In printf, can have \* instead of size and/or precision

Then, size/precision is given by next argument:

printf("`%. *s`", max, s); prints at most max chars

## Sample formatted output

Floating point numbers in various formats:

```
printf("%f\n", 1.0/1100); // 0.000909 : 6 decimal digits
printf("%g\n", 1.0/1100); // 0.000909091 : 6 significant dig.
printf("%g\n", 1.0/11000); // 9.09091e-05 : 6 significant dig.
printf("%e\n", 1.0); // 1.000000e+00 : 6 decimal digits
printf("%f\n", 1.0); // 1.000000 : 6 decimal digits
printf("%g\n", 1.0); // 1 : no period and useless zeroes
printf("%.2f\n", 1.009); // 1.01: 2 decimal digits
printf("%.2g\n", 1.009); // 1: 2 significant digits
```

Writing integers in table form:

```
printf("|%6d|", -12); | -12| printf("|% d|", 12); | 12|
printf("|%-6d|", -12); |-12| printf("|%06d|", -12); |-00012|
printf("|%+6d|", 12); | +12|
```

Write 20 characters (printf returns count of written chars)

```
int m, n, len = printf("%d", m); printf("%*d", 20-len, n);
```

## Examples of formatted input

Two characters separated by a single space (consumed by `%*1[ ]`)

```
char c1, c2; if (scanf("%c%*1[ ]%c", &c1, &c2) == 2) ...
```

Read an int with exactly 4 digits: `unsigned n1, n2, x;`

```
if (scanf("%n%4u%n", &n1, &x, &n2) == 1 && n2 - n1 == 4) ...
```

`%n` counts read chars; store counters in `n1, n2`, then subtract

Reads/checks for a word that must appear: `int nr=0;`

```
scanf("http://%n", &nr); if (nr == 7) { /*appears */}
```

```
else { /* does not reach %n, nr stays 0 */}
```

Ignores up to (and excluding) a given char (`\n`):

```
scanf("%*[^\\n]");
```

Test for the right number of read objects, not just nonzero!

```
if (scanf("%d", &n) == 1), not just if (scanf("%d", &n))
```

`scanf` may also return EOF, which is nonzero!

For integers, test overflow using `extern int errno;`

```
#include <errno.h> // declares errno and error codes
```

```
if (scanf("%d", &x) == 1) // test reset errno on overflow
```

```
    if (errno == ERANGE) { printf("number too big"); errno = 0; }
```

## ERRORS with reading from input

**NO!** ~~while (scanf("%...", ...))~~ DON'T test for nonzero result. It could be  $> 0$  (items read), or  $-1$  (EOF), nothing read!

YES: `while (scanf("%...", ...) == how-many-items-wanted)`

**NO!** ~~scanf("%20[a-z]s", buf).~~ The format is `[]`, not `[]s`

YES: `if (scanf("%20[a-z]", buf) == 1) ...`

**NO!** ~~scanf("%20s,%d", name, &grade).~~ The `s` format reads everything non-whitespace, so it won't stop at comma

YES: `if (scanf("%20[^,],%d", name, &grade) == 2)`

to read a string with no comma (all else allowed, including whitespace), the comma, and a number